

Power Flow Analysis



Execute power flow analysis on threephase electric power networks

The CYME Power Flow software is the power flow analysis module of the CYME power engineering software for the analysis of three-phase electric power networks. It is equipped with powerful analytical options and alternative solution techniques. The objective of a power flow program is to analyze the steady-state performance of the power system under various operating conditions. It is the basic analysis tool for the planning, design and operation of any electrical power system, be they distribution, industrial or transmission networks.

The Power Flow software utilizes state-of-the-art sparse matrix/ vector methods and multiple solution algorithms:

- Full Newton-Raphson
- · Fast Decoupled
- Gauss-Seidel

The Power Flow program is the main module of the CYME software for the analysis of industrial and transmission power systems, and it has a seamless interface with other modules such as:

- Fault Analysis: for fault studies taking into account pre-fault system loading
- Harmonic Analysis: for the calculation of the fundamental frequency voltage and current profiles required for harmonic distortion indices calculations
- Transient Stability: to set the initial condition of the system as required by the network control models for transient stability studies
- Dynamic Motor Starting module: to account for system wide voltage drops during induction and synchronous motor starting studies





Power Flow Analysis

Execute power flow analysis on three-phase electric power networks

- Features
 - Analyzes networks with thousands of buses and branches
 - Multiple swing buses allowed
 - Automatic swing bus selection for isolated subsystems
 - Simultaneous solution for islanded networks
 - Detailed equipment modeling of induction and synchronous motors, variable frequency drives, bus ways and all necessary network elements for an accurate representation of the network
 - Synchronous generator
 - Reactive power limits and remote voltage control
 - Generator reactive power capability curves
- Local or remote control of voltage and reactive power flow through tap changing transformers
- Phase angle shift transformer with active power control
- Cogeneration modeling including:
 - Induction generators
 - Wind Energy Conversion Systems (WECS)
 - Photovoltaic (PV Cells)
 - Fuel cells
 - Micro-turbines
- Comprehensive representation of DC transmission lines with rectifier and inverter controls
- Flexible AC Transmission Systems (FACTS) representation of:
 - Static synchronous compensator (STATCOM),
 - Unified Power Flow Controller (UPFC)

- Customer load model library manager for any type of load model including:
 - Constant power, constant current and constant impedance
 - Composite load model
 - Voltage sensitivity exponent load model
- Capacitors with the following control types: voltage, current, reactive current, reactive power, power factor, temperature and time-controlled
- Switchable shunt banks of both capacitive and inductive elements
- Scaling factors applied to the generators and to the loads on the whole network or by zone
- Global parameters to include or exclude any types of equipment from the analysis



Generator Capability Curves



Power Electronics - FACTS



Power Electronics - DC Systems

- Five limit categories for nominal, planning, emergency loading or any user-defined criteria
- User-defined units for bus voltages, generator productions and branch flows on both one-line diagrams and tabular reports
- Tabular reports can also be directly exported to other spreadsheet programs such as Microsoft Excel®
- Color coding on the network one-line diagram as per userdefined criteria; for example:
- Overloaded equipment
- Voltage violations of buses and nodes
- Visualization of conductor rating that may reflect, for example, improperly sized cables
- System voltage levels

Eaton

Powerina Business Worldwide

1000 Eaton Boulevard Cleveland, OH 44122 United States Eaton.com

CYME International T&D

1485 Roberval, Suite 104 St.Bruno, QC, Canada J3V 3P8 P: 450.461.3655 F: 450.461.0966 P: 800.361.3627 (Canada/USA) CymeInfo@eaton.com www.eaton.com/cyme

© 2017 Eaton All Rights Reserved Printed in Canada Publication No. BR 917 012 EN February 2017 Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information

